





Battery System Designed For PV Household Application

Battery Series

M4860



-  Plug & Play
-  Modular
-  Safety
-  Long Lifetime

Physical

Model	M4860
Battery Type	LiFePO ₄ (LFP)
Battery Manufacturer	LISIEN Power Your Life!
System Weight	40 kg
Dimension (W x D x H)	482 x 460 x 156 mm
Protection Level	IP20

Electrical

Energy Capacity	3.0 kWh
Usable Capacity	2.7 kWh
DOD	90%
Nominal Voltage	51.2 V
Operation Voltage Range	44.8 - 58.4 V
Internal Resistance	≤50 mΩ
Cycle Life	≥8000

Warranty

Product Warranty	5 Years
Performance Warranty	10 Years

BMS

Power Consumption	<2 W (Work) <100 mW (Sleep)
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature.
SOC	Intelligent algorithm
Communication	CAN and RS485 compatible

System Configuration

Module Parallel	1 ~ 6 Parallel
Capacity Range	3/6/9/12/15/18 kWh

Operation

Max. Charge Current	30 A (0.5C)
Max. Discharge Current	30 A (0.5C)
Operating Temperature Range	-10 C ~ 50 C
Transport Or Storage Temperature Range	-10 C ~ 45 C
Humidity	15% ~ 85%

Cabinet

Dimension (W x D x H)	600 x 600 x 990/1390 mm
Max. Modules	4/6
Color	Black
IP Protection Class	IP20



Headquarters:

+86 (0)513 806 868 91
 info@alpha-ess.com
 www.alpha-ess.com
 JiuHua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Germany:

+49 (0)6103 / 459 160-1
 europe@alpha-ess.de
 www.alpha-ess.de
 Paul-Ehrlich-Straße 1a,
 63225 Langen, Hessen

Australia:

+61 1300 968 933
 australia@alpha-ess.com
 www.alpha-ess.com.au
 Suite 2, Level 1, 530 Botany Road,
 Alexandria, NSW, 2015



Official Website



WeChat